



Industrial Thermotubix®

Thick wall, knitted fibreglass sleeving

Applications

Thermotubix Industrial is a thick wall, knitted fibreglass sleeving with an external coating of flame retardant silicone rubber.

Thermotubix provides effective protection against sustained high temperatures, flames and molten metal splashes, that can seriously damage electrical cables and hydraulic, gas and lubricant supply lines.

Thermotubix Industrial is used in the steel, petrochemical and motorsport industries, to protect against internal and external hazards, especially contact with hot surfaces.

Operating Temperature

- -54°C to +260°C

Features & Benefits

- Highly flexible

Industrial Thermotubix Dimensions (all dimensions are in mm's)

| Description | Internal Diameter (mm) | Standard Packaging (mm) | Ordering Description |
|-----------------------------|------------------------|-------------------------|---------------------------|
| Industrial Thermotubix 8 | 8 | 15 | THERMOTUBIX-IND-8mm-12 |
| Industrial Thermotubix 9.5 | 9.5 | 15 | THERMOTUBIX-IND-9.5mm-12 |
| Industrial Thermotubix 12.7 | 12.7 | 15 | THERMOTUBIX-IND-12.7mm-12 |
| Industrial Thermotubix 16 | 16 | 15 | THERMOTUBIX-IND-16mm-12 |
| Industrial Thermotubix 19 | 19 | 15 | THERMOTUBIX-IND-19mm-12 |
| Industrial Thermotubix 22 | 22 | 15 | THERMOTUBIX-IND-22mm-12 |
| Industrial Thermotubix 25 | 25 | 15 | THERMOTUBIX-IND-25mm-12 |
| Industrial Thermotubix 32 | 32 | 15 | THERMOTUBIX-IND-32mm-12 |
| Industrial Thermotubix 38 | 38 | 15 | THERMOTUBIX-IND-38mm-12 |
| Industrial Thermotubix 45 | 45 | 15 | THERMOTUBIX-IND-45mm-12 |
| Industrial Thermotubix 51 | 51 | 15 | THERMOTUBIX-IND-51mm-12 |
| Industrial Thermotubix 57 | 57 | 15 | THERMOTUBIX-IND-57mm-12 |
| Industrial Thermotubix 64 | 64 | 15 | THERMOTUBIX-IND-64mm-12 |
| Industrial Thermotubix 76 | 76 | 15 | THERMOTUBIX-IND-76mm-12 |
| Industrial Thermotubix 89 | 89 | 15 | THERMOTUBIX-IND-89mm-12 |
| Industrial Thermotubix 101 | 101 | 15 | THERMOTUBIX-IND-101mm-12 |

Note: Industrial Thermotubix is also available with an indelible ink marking, for more information please contact IS-Rayfast.

Ordering Information

Standard colour: 12 = (Red iron oxide).

Ordering description: Specify product name, size and colour; **THERMOTUBIX-IND-16mm-12**.

Ordering Example: A red iron oxide protective sleeve capable of covering a 48mm cable diameter is required = **THERMOTUBIX-IND-51mm-12** (12=Red iron oxide).