



Y

General purpose +105°C PVC tubing

Applications

A tough and flexible general purpose tubing providing good insulation resistance. Suitable for electrical insulation on cable harnesses.

Features & Benefits

- Low temperature flexibility
- Wide range of colours & sizes available

Operating Temperature

- -40°C to +105°C

Installation

- Roll on application, no heat required

Specifications/Approvals

- BS2848 Type 3 Class 105T

Dimensions (all dimensions are in mm's)

Inside Diameter	Wall Thickness	Standard Packaging & Ordering Description	
As Supplied (nom)	Wall Recovery (nom)	Spool Pack Size (SP)	Ordering Description
2.0	0.5	100m	Y-2.0/0.5-Colour
3.0	0.5	100m	Y-3.0/0.5-Colour
4.0	0.5	100m	Y-4.0/0.5-Colour
5.0	0.5	100m	Y-5.0/0.5-Colour
6.0	0.5	100m	Y-6.0/0.5-Colour
7.0	0.5	100m	Y-7.0/0.5-Colour
8.0	0.5	100m	Y-8.0/0.5-Colour
9.0	0.5	100m	Y-9.0/0.5-Colour
10.0	0.5	100m	Y-10.0/0.5-Colour
12.0	0.5	100m	Y-12.0/0.5-Colour
15.0	0.5	100m	Y-15.0/0.5-Colour

Note: Additional sizes, wall thickness and cut pieces are also available on request.

Ordering Information

Standard colours: 0 = (Black), 2 = (Red), 4 = (Yellow), 5 = (Green), 6 = (Blue), 9 = (White), X = (Clear).
 Size selection: The smallest size that provides the best fit (non heat-shrinkable).
 Standard packaging: Spools (SP).
 Ordering description: Specify product, size and colour; e.g. **Y-4.0/0.5-0** (0=Black).
Ordering Example: Tubing to fit a cable diameter O/d of 10mm = **Y-10.0/0.5-2** (2=Red).